

HGMak



Serial A
Ambalaj Üretim Makinaları
Pouch Making Machines
www.hgmak.com

Tam Otomatik Ambalaj Üretim Makinaları

A serisi, doypack, 3 veya 4 yandan yapılandırılmış zipli hazır paket ihtiyacı için üretilmiş olup, özel ek fonksiyonları ile özel şekilli, emzikli paketler de üretebilen, servo kontrollü yüksek kapasiteli makinalardır.

A Serisi Genel Özellikler :

- ✓ Otomatik film merkezleme sistemi
- ✓ Servo kontrollü sistem hareketleri
- ✓ Mekanik makas sistemi
- ✓ Fotoselli izleme ve kontrol sistemi
- ✓ Zip uygulama sistemi (Opsiyonel)
- ✓ Zip delik delme sistemi (Opsiyonel)
- ✓ Zip açma sistemi (Opsiyonel)
- ✓ Köşe yuvarlatma sistemi (Opsiyonel)
- ✓ Çentik açma sistemi (Opsiyonel)
- ✓ Askılık deliği (Eurohole, Yuvarlak veya Çanta) açma sistemi
- ✓ LCD dokunmatik kontrol işletim sistemi
- ✓ Paket sayma ve dizme sistemi (Opsiyonel)
- ✓ Ürün çıkış sistemi
- ✓ Krom Paslanmaz Gövde
- ✓ CE standartlarına uygunluk

A Serisi Teknik Özellikler :

Paket Eni	Paket Boyu	Paketleme Hızı	Bobin Çapı
Min. 80 mm Max. 320 mm	Min. 100 mm Max. 400 mm	40-60 paket/dakika	Max. 600 mm

* Paket ölçüleri modele göre değişmektedir.

* Hız dubleks, tribleks modellerle 2 ya da 3 kat artırılabilir.

* Bilgilerde değişiklik yapılabilir.

Fully Automatic Pouch Making Machines

The servo driven A series is produced for the need of pre-made bags as doypack (stand-up pouches), 3 or 4 side sealed pouches with zipper closures. Also with special additional functions, it can produce special shaped and spouted pouches.

A Series General Specifications :

- ✓ Film centering system
- ✓ Servo controlled main systems
- ✓ Mechanical scissors
- ✓ Photocell control system
- ✓ Zipper application (Optional)
- ✓ Zipper perforation system (Optional)
- ✓ Zipper opening system (Optional)
- ✓ Round corner application (Optional)
- ✓ Tear notch system (Optional)
- ✓ Euro or Punch hole application (Optional)
- ✓ LCD touch control operation system
- ✓ Premade bags sorting and counting system (Optional)
- ✓ Output Conveyor
- ✓ Stainless steel machine body
- ✓ Accordance with CE Standarts

A Series Technical Specifications :

Bag Width	Bag Length	Operation Speed	Reel Diameter
Min. 80 mm Max. 320 mm	Min. 100 mm Max. 400 mm	40-60 bag / minute	Max. 600 mm

* Package size can changes according to the model.

* Speed can be increased to 2 or 3 times by dublex or triblex models.

* All info subject to change.

Standart Doypack Standard Doypack	Zipli Doypack Doypack With Zipper	Askı Delikli Doypack Doypack With Eurohole	Köşeden Emzikli Doypack Doypack With Corner Spout	Üstten Emzikli Doypack Doypack With Top Spout	Zarf Paket Flat Pouch
					